

M | Vertical Endeavour PRODUCT SPECIFICATIONS

COLLECTION NAME	Vertical Endeavour
STYLE NUMBER	I0546
PRODUCT TYPE	Wallcovering
CONSTRUCTION	Needlebond
FIBER TYPE	50% olefin / 50% PET polyester
DYE METHOD	100% Solution Dyed
SECONDARY BACKING	SBR latex

TOTAL WEIGHT	30 oz/ly
ROLL SIZE	72 ft x 54 in
PACKAGING	"crush proof" box

Performance Testing

FLAMMABILITY	Passes Corner Burn NFPA-265; UBC 8-2 Tunnel test. Class A Rating ASTM E-84	
ACOUSTICAL	ASTM C-423-84A Gypsum Board NRC .20 Acoustical Board NRC .80 (When installed using Shaw 5036 adhesive)	
TENSILE STRENGTH	ASTM D-5034, (LBS) Break 142 L x 132 W	Elongation 195 L x 145 W
TEAR (TRAP) STRENGTH	ASTM D-2261 (LBS) 30 L x 25 W	
ABRASION RESISTANCE	ASTM D-3884 Ribs # Cycle 1,720	Rapture # Cycles 2,260
COLORFAST	AATCC-165 Wet Crocking 5	Dry Crocking 5
FMVSS 302	Passes	
ELECTROSTATIC	AATCC-134 0.2kv	

Warranty

One Year Limited Warranty

Please visit patcraft.com for the most current warranty information.

Installation Methods

Direct Glue